

WORLD CAT 290EC



HIN	MODEL YEAR	LOA	BEAM	HULL DRAFT
USEPY03125K910	2010	29' 1"	9' 6"	15"

Approx. Dry Weight	Fuel Capacity	Trailer Height w/ top	Freeboard Aft	Freshwater Cap.	Wastewater Cap.
9,700 lbs w/ twin 250's	2 x 125 gal	10' 6" (est.)	27"	35 gal	15 gal

STANDARD FEATURES

Power

- Suzuki 250 4-Stroke Package (Twin counter rotating engines, rigging, controls & stainless props)

Bow

- Molded-in bow pulpit with roller and cleats
- Molded-in bow seating with cushion
- Raised toe-kick for added safety
- Fully welded 316 marine-grade stainless steel grab rail
- (2) additional 500-gph forward bilge pumps with auto switches

Cabin

- Full cabin featuring master berth, galley, integrated storage, stylish fabrics and lighting
- Enclosed, lockable head compartment with direct access to the cabin and helm. Marine head with a 15-gallon holding and over-board discharge. Standing freshwater shower, vanity with Corian countertop and stainless sink, cabinetry and mirror.
- Cabin storage includes port and starboard under berth drawer storage and end tables with port and starboard drawer storage
- Galley package includes Corian countertop, refrigerator, microwave, stainless steel sink, and storage
- Standard shorepower connection featuring 50-amp service and cordset, AC panel with digital meter and battery charger
- 35-gallon freshwater system with water heater
- Aluminum deck hatches with screens and shades

Helm

- Full wrap-around tempered safety glass windshield
- Pantograph-style heavy-duty waterproof windshield wiper with rinse
- Non-slip anti-fatigue mat to reduce the stress of standing on the hard surface
- Centerline helm including dual helm seat with dual stand-up bolster and ergonomic dash layout capable of twin 8" screens or one 12" screen
- (4) batteries stored center under the helm (additional house battery increases reliability and longevity of the battery bank)
- 42-gallon insulated, re-circulating livewell with a 1100-gph magnetic drive pump, overboard drain and clear lid
- Port and starboard cabin bi-fold entry doors
- Magnetic catches on cabin/head entry and walk-through doors
- Port and starboard tackle and gear storage in helm area
- (2) 250-quart insulated deck fishboxes with macerator pumps (port and starboard)
- Electronics package to monitor tanks and battery bank
- Cast Stainless Steel Edson Wheel with Power Knob and power-assist steering

Stern

- Euro-style transom with heavy-duty acrylic door, bait prep, and tool storage
- Port and starboard sealed-off fuel filter compartments for easy maintenance
- Port and starboard cockpit storage compartments with tackle and bulk options
- Integrated cockpit step for easy in-and-out access
- (6) gunnel-mounted stainless steel rod holders
- (6) pull-up stainless steel cleats with backing plates
- Freshwater transom shower

WORLD CAT 290EC



HIN	MODEL YEAR	LOA	BEAM	HULL DRAFT		
USEPY03125K910	2010	29' 1"	9' 6"	15"		
Approx. Dry Weight	Fuel Capacity	Trailer Height w/ top	Freeboard Aft	Freshwater Cap.	Wastewater Cap.	
9,700 lbs w/ twin 250's	2 x 125 gal	10' 6" (est.)	27"	35 gal	15 gal	

OPTIONAL EQUIPMENT

- Fiberglass top with aluminum frame, integrated radio box, recessed lighting, rocket launchers, and spreader lights
- Fischer Panda® 4.2kW diesel generator with 10-gallon fuel tank (replaces port fishbox)
- High grade full enclosure curtain package with Strataglass
- Cruiseair® 8,000 BTU heating/ cooling unit with vents to the cabin, head and cockpit
- Pro series freetail windlass with 300' line, 15' chain, 22lb anchor, and foot switches at the deck
- Carolina Blue two-tone hull color
- Dual aft fold-down seating with backrest cushions
- Extended swim platform with integrated handrails and ladder
- Clarion Stereo system with 4 speakers, Sirius Satellite, and an iPod or MP3 port

WORLD CAT 290EC



HIN	MODEL YEAR	LOA	BEAM	HULL DRAFT	
USEPY03125K910	2010	29' 1"	9' 6"	15"	
Approx. Dry Weight	Fuel Capacity	Trailer Height w/ top	Freeboard Aft	Freshwater Cap.	Wastewater Cap.
9,700 lbs w/ twin 250's	2 x 125 gal	10' 6" (est.)	27"	35 gal	15 gal

KEY STANDARD EQUIPMENT

Construction

- Patented Vectorflo® semi-displacement hull provides a dry, stable, high-performance ride
- Our Unibody Construction® fuses the hull and deck to maximize hull rigidity and strength for the life of your World Cat
- Ten-year limited, transferable, structural hull warranty
- All World Cat helms are ergonomically designed using our CAD system to provide comfortable placement of controls, gauges, and electronics while assuring excellent bow visibility per ABYC guidelines. A
- Full 316 stainless steel hardware package provides a lifetime warranty against structural corrosion for years of carefree use
- 100% composite construction creates a solid, durable, rot-free platform for serious offshore performance
- 100% composite transom reinforced with aluminum backing plates to hold up the stresses of high-horsepower engines
- Large diameter PVC rigging tubes provide ample room for the rigging of electronics, while providing excellent chafe protection for the electrical systems
- LED cockpit and navigational lighting for years of trouble-free boating
- Chrome-plated, epoxy-coated stainless steel fasteners throughout for long-term performance and appearance
- All cleats and rod-holders are through-bolted with backing plates for heavy-duty marine use
- All wires are labeled every 3 inches for ease of maintenance and serviceability
- Premium marine grade vinyl and foam used on all upholstery to provide years of good looks and easy care
- Full upholstery kit includes aft coaming pads on all boats and forward coaming pads on center consoles
- Livewells and fishboxes are double insulated with composite coring and urethane foam for consistent temperature control
- Hydraulic steering system with tilt-helm, dual steering cylinders, and a liquid tie-bar
- (8) stainless steel recessed cleats provide maximum holding power and minimum interference with fishing lines
- (4) pop-up fender cleats (290EC has 2 cleats)
- Bow anchor locker for convenient storage of chain and rode
- Minimum of two (2) twist lock 12V DC plugs in the cockpit for downriggers, electric reels, kites, or drink blender (TE's include four)
- Stainless steel cup holders
- Raw and fresh water systems

Safety

- All World Cats are NMMA certified following ABYC standards while all models over 26 feet are Yacht Certified for added safety
- Four (6) straight Marine Industry CSI Awards for fiberglass outboard boats from 2004 to 2009
- Customer care package including Coast Guard kit, four (4) fenders, six (6) dock lines, and batteries
- Independent propulsion, fuel, and electrical systems for the added security that you will be able to return home safely on one engine
- Battery management system monitors and charges all three (3) battery banks while allowing for emergency paralleling for increased safety.
- Heavy-duty wiring systems meet or exceed all NMMA requirements and include tinned copper wiring, Deutsch® sealed connectors, and wires labeled every three inches
- Non-corrosive, polyethylene fuel tanks, which will not rust or corrode in the harsh salt-water environment
- Self-bailing cockpits with a minimum of four (4) oversized drains utilizing gravity to quickly drain your deck
- Minimum of two (2) 1500-gph bilge pumps with automatic float switches quickly evacuate the hull to keep you safe and your hull dry in almost any situation
- Break-away dive ladder for easy transom entry is standard on all models for added safety and convenience
- Water-resistant bilge hatches with compression gaskets in motor-wells to provide bilge pump access and serviceability
- Molded-in diamond pattern non-skid on all walking surfaces provide enough grab for safety without hurting your feet
- Toe-rails to increase cockpit floor-space and fishability while improving comfort and safety (not available on the 270SD)